


Affordable Titanium – A TIMET Perspective



Titanium in Transportation

- A Proven Weight Saving Solution in high performance automotive
- Cost premium for installed components is 2X to 10X vs. incumbent metals
- Transition to sustained series production not yet achieved



Corrosion Resistance

A reprint of an article published in the Sept. 26, 2005 issue of American Metal Market



Titanium 2005

Vrrrrr000000mmm

Every ounce counts on Yamaha's meanest motocross bike

LOS ANGELES — Another landmark in the consumer vehicle market has been claimed for titanium with the addition of

the rear suspension spring on By Frank | production versions of certain Yamaha Motor Co. Ltd. Haflich motorcycles.

Titanium Metals Corp. (Timet), Denver, said the 2006 Japanesebuilt Yamaha YZ model motocross bikes are the first cycles anywhere with titanium springs as original equipment.

Made of Timetal LCB (low-cost beta), an alloy supplied by the company's Timet Automotive unit in Morgantown, Pa., the "shock springs" typically weigh 30 percent less than their chrome-silicon-steel counterparts on Yamaha's comparable 2005-model bikes

As its name indicates, Timetal LCB (6.8) molybdenum-4.5 iron-1.5 aluminum) is a lower-cost version of high-strength Beta-C titanium originally developed for aerospace uses. Its first automotive application was in rear suspension springs on the 2001 Volkswagen Lupo FSI and, more recently, the 2004 Ferrari Challenge Stradale, its initial use on a production car.

The springs are supplied to lwata, Japan,-based Yamaha by Chuo Spring Co. Ltd., Nagoya, Japan. Timetal LCB is typically melted at Timet's Henderson. Nev., operations, but Timet emphasizes that it is capable of producing the alloy in all of its melt shops around the world. While conversion of LCB ingot into billet has taken place both at Timet and externally, Timet's source for rolling the billet into elastically wound wire coils has been Perryman Co.,



'SHOCK SPRINGS': The YZ models are the first cycles anywhere outfitted with titanium springs as original equipment.

Washington, Pa.

Kurt Faller, president of Timet Automotive, said the new Yamaha suspension spring is evidence that titanium "offers proven and straightforward solutions to a variety of weight-reduction and performance-improvement challenges.

The Timetal LCB springs are wound into shock springs on automatic computer numerical control (CNC) machines the

LCB for the 2006 Yamaha YZ450

- Formulated for affordable performance using low cost raw materials
- Manufactured using continuous processing for economies of scale
- Spring wound on CNC machines used for steel
- Delivers affordable weight savings for high performance vehicles.
- Not sustained due to lack of infrastructure





Corvette Z06 – 2001/02

- Corvette Z06 Needed Mass Reduction to Meet Performance Objectives and Emissions Regulations
- Focus was to Achieve a Target \$/Mass Saved Goal
- TIMET Worked Extensively with Arvin to Streamline Manufacturing
- Tested and Evaluated Components with a "Fit for Purpose" Attitude
- Minimizing Material Consumption/Scrap Allowed Arvin to find \$2
 Million Savings in Standard Stainless Muffler Production
- Met GM Cost Target (\$/Mass Saved) without Marketing or other Considerations
- Supported rate of 10,000 per year
- Not able to transition to higher volumes due to growing aero demand.



1. Engine for testing titanium connecting rods

2. Variation of design

3. Run out of thread

4. Typ of thread

5. Bore

6. Fretting piston - connecting rod

Fretting bearing - connecting rod

8. Preproduction



1,6 L – 92kW- engine

application:

Lupo - GTI





engine test

on road test V

Proposed to VW Management for Standard Production circa 2002 VW leadership changed and focus moved away from titanium technology

M. Scholz et al Titanium 2003



Integrated Development Approach.

Aligned Strategy and focused funding required

Alternate extraction for novel product forms

Reduced cost raw materials

Reduced cost extraction

Alloys for high performance

Accelerated insertion tools

Alloys for Affordable Performance

Near net & prototype Manufacturing High volume manufacturing for economies of scale

Tailored manufacturing for specific affordable performance



Key Points

Cost of titanium metal units is between 40 and 60% of mill products and more for components with high "buy to drive" ratio

Lower the cost of metal units

Cost to manufacture: Individual applications can be made attractive by innovating in the design and manufacturing space.

Integrated, innovative "Fit for Purpose" approach Recognize and plan for the infrastructure challenges

Transition to series production requires sustained and consistent industry strategy and targeted funding

Learn from the aluminum experience